



Contents lists available at ScienceDirect

## Composites: Part B

journal homepage: [www.elsevier.com/locate/compositesb](http://www.elsevier.com/locate/compositesb)

## Erratum

## Erratum and addendum to “Practical expressions for the design of laminated glass” [Compos. Part B: Eng. 45 (2013) 1677–1688]

Laura Galuppi<sup>a</sup>, Giampiero Manara<sup>b</sup>, Gianni Royer Carfagni<sup>a,\*</sup><sup>a</sup> Department of Industrial Engineering, University of Parma, Parma, Italy<sup>b</sup> Permasteelisa Group, Vittorio Veneto, Italy

Due to an unfortunate turn of events, the article referred to in the title was published with typos in some values of coefficient  $\Psi$  ( $\text{mm}^{-2}$ )  $\times 10^6$  appearing in Tables 2.1 and 2.2. In the following pages the reader can find the correct version of the tables. Consequently, the sentence at the end of page 1682, “For example, the value of coefficient  $\Psi$  for a plate of dimension 3000 mm x 1800 mm, supported on 3000 mm edge, can be found in Table 2.2 by choosing  $a = 3000$  mm,  $\lambda = 0.6$ ” has to be changed to “For example, the value of coefficient  $\Psi$  for a plate

of dimension 3000 mm x 1800 mm, supported on a 1800 mm edge, can be found in Table 2.2 by choosing  $a = 3000$  mm,  $\lambda = 0.6$ ”.

Furthermore, since *large* panes of structural laminated glass are more and more frequently used in architectural works (the largest available laminated glass size, restricted by autoclave size, substrate or base product size and type is usually 6 m), tables have been improved and updated by considering values of the length of the plate edge up to 6 m.

DOI of original article: <http://dx.doi.org/10.1016/j.compositesb.2012.08.010>

\* Corresponding author.

E-mail address: [gianni.royer@unipr.it](mailto:gianni.royer@unipr.it) (G. Royer Carfagni).